



Notes:

- 316 SS, 18-8 Fasteners, Plastics and Elastomers
- Weight = 4.4 Lbs
- Nozzle Sizes: Range from .100" to .200"
- Pressure Range: 50 to 70 PSIG (7 to 70 bar)
- Flow Range: 5 to 6 GPM
- Min. Full Wash Cycle: 3.5 minutes
- Clearance: Designed to fit through a 2" (50mm) bung hole
- Temperature: 180°F (82°C) Max.

UNLESS OTHERWISE SPECIFIED		GAMAJET CLEANING SYSTEMS, INC.	
* DIMENSIONS ARE IN INCHES		604 Jeffers Circle	
* DIMENSIONS REFERENCE THEORETICAL SHARP CORNERS		Exton, PA 19341	
* FILLET RAD.: 0.015 ±0.005		NAME	
* TOLERANCES:		GAMAJET GENTLEJET	
.XX ±0.01		EQUIPMENT	
.XXX ±0.005		GAMAJET HD-BB	
ANGLE ±0.5°		DRAWN BY	
MATERIAL:		GES	
316 SS		DRAWN DATE	
FINISH (UNLESS OTHERWISE SPECIFIED):		6/24/2011	
32 Ra		REV	
SCALE 1:3		02	
		DWG. NO.	
		GJ HDBB-1000-LP CS	
		SHEET 1 OF 1	

THIS DRAWING IS THE PROPERTY OF GAMAJET CLEANING SYSTEMS, INC. REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

REVISIONS TABLE			
DRAWN BY	DATE	REV.	DESCRIPTION
GES	6/24/11	1	NEW RELEASE
GES	12/15/11	2	CHANGED DOCUMENT NAME FROM LOW PRESSURE GAMAJET HD-BB