



**NOTES:**

- 316 SS MAIN BODY PARTS, 18-8 SS FASTENERS, PLASTICS & ELASTOMERS
- WEIGHT: 10 lbs
- INLET: 1-1/2" SANITARY INLET(SHOWN) & 2" CAMLOCK ADAPTER/1-1/2" FNPT
- FLOW RANGE: 30-120+ GPM
- PRESSURE: 30-500+ PSI
- MINIMUM FULL WASH CYCLE: 8-15 MINS
- DUAL NOZZLE MACHINE AVAILABLE
- CLEARANCE: 7" ID

THIS DRAWING IS THE PROPERTY OF GAMAJET CLEANING SYSTEMS, INC. REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

REVISIONS TABLE			
DRAWN BY	DATE	REV.	DESCRIPTION
SAM	11/10/10	1	INITIAL RELEASE: CUT SHEET

UNLESS OTHERWISE SPECIFIED  
 \* DIMENSIONS ARE IN INCHES  
 \* DIMENSIONS REFERENCE THEORETICAL SHARP CORNERS  
 \* FILLET RAD.: 0.015±0.005  
 \* TOLERANCES:  
 .XX ±0.01  
 .XXX ±0.005  
 ANGLE ±0.5°

MATERIAL:  
 316 SS  
 FINISH (UNLESS OTHERWISE SPECIFIED):  
 32 Ra  
 SCALE 1:5

<b>GAMAJET CLEANING SYSTEMS, INC.</b> 604 Jeffers Circle Exton, PA 19341			
NAME <b>GAMAJET POWERFLEX CUT-SHEET</b>			
EQUIPMENT <b>GAMAJET POWER-FLEX</b>			
DRAWN BY <b>SAM</b>	DRAWN DATE <b>11/10/2010</b>	REV <b>1</b>	
DWG. NO. <b>10-1110 POWER-FLEX</b>			SHEET 1 OF 1